

High Density Building Insulation

with ECOSE™ Technology

Submittal Date _____

KNAUF INSULATION

Product Provided

EcoBatt™ Insulation with ECOSE™ Technology

High density glasswool insulation is specifically designed for sidewall, cathedral ceiling and floor applications where optimal thermal performance is required, and space for insulation is limited. Knauf High Density (HD) Ecobatt products offer a superior thermal value per inch as compared to standard building insulation products.

R-15-3½" High Density EcoBatt batts are designed for use in 2 x 4 framed wall sections. R-21-5½" High Density batts are designed for use in 2 x 6 framed sidewalls and floor assemblies, where air spaces are neither required nor desired. R-30-8¼" High Density Cathedral Ceiling batts are designed for use in 2 x 10 framed cathedral ceiling or floor assemblies where a 1" air space is required. R-38-10¼" High Density Cathedral Ceiling batts are designed for use in 2 x 12 framed cathedral ceiling or floor assemblies where a 1" air space is required.

○ Unfaced HD EcoBatt Insulation

Glasswool insulation is designed to be friction fit between framing members. They can be used in applications with specifier permitted choice of warm side vapor retarders, including foil backed gypsum board or polyethylene film.

Unfaced High Density glasswool insulation is also an excellent sound control insulation, designed for installation in partition walls and floor assemblies, it will serve to retard the transmission of airborne noise.

When tested in accordance with ASTM E 84, material has a Fire Hazard Classification of 25/50 or less.

Complies with the requirements of the applicable ASTM and cancelled federal specifications:

ASTM C 665, Type I, Class A

HH-I-521F, Type I, Class A

ASTM E 136

- 3½" R-15HD ○ 8¼" R-30HD
- 5½" R-21HD ○ 10¼" R-38HD

○ Kraft Faced HD EcoBatt Insulation

Glasswool insulation with asphalted kraft paper with stapling flanges. Kraft vapor retarder has vapor transmission (permeance) rating of 1.0 or less.

Kraft Faced High Density glasswool insulation is also an excellent sound control insulation, designed for installation in partition walls and floor assemblies, it will serve to retard the transmission of airborne noise. Kraft facing will burn and should be covered with an approved finish material, and should not be left exposed.

Complies with the requirements of the applicable ASTM and cancelled federal specifications:

ASTM C 665, Type II, Class C

HH-I-521F, Type II, Class C

- 3½" R-15HD ○ 8¼" R-30HD
- 5½" R-21HD ○ 10¼" R-38HD

ECOSE™ Technology Description

ECOSE Technology is a revolutionary new organic binder that contains no phenol, formaldehyde, acrylics or artificial colors. It is made from rapidly renewable organic materials instead of oil-based chemicals for greater sustainability.

Thermal Performance

Thermal resistance (R-value) of the blanket insulation only is certified to be as represented above when measured at a mean temperature of 75°F (24°C) and subject to manufacturing and testing tolerances.

Fiber Glass and Mold

Glasswool insulation will not sustain mold growth. However, mold can grow on almost any material when it becomes wet and contaminated. Carefully inspect any insulation that has been exposed to water. If it shows any sign of mold it must be discarded. If the material is wet but shows no evidence of mold, it should be dried rapidly and thoroughly. If it shows signs of facing degradation from wetting, it should be replaced.

Quality Assurance

On-line production is periodically tested to ensure that Knauf insulation delivers the stated thermal performance or better when properly installed at the label thickness.



Knauf High Density EcoBatt™ Building Insulation is certified for indoor air quality as a low emitting product by The GREENGUARD Environmental Institute to both the GREENGUARD Certification ProgramSM and the more stringent GREENGUARD For Children and SchoolsSM standard. www.greenguard.org

