

Product name: Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application Page: 1/12  
Revision Date: 2015-06-23 Print date: 2015-10-23  
P/N-no.: KI\_DP\_112 SDS-ID: US-EN/1.1

---

## **SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

### **Product identifier**

Product name: Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application

Synonyms, trade names: AssureR® & StableR®

Revision: Date: 2015-10-23

### **Relevant identified uses of the substance or mixture and uses advised against**

Identified uses: Thermal and/or acoustic insulation for use in technical applications, industrial applications and in building construction.

Uses advised against: None known.

### **Details of the supplier of the safety data sheet**

Head Office Knauf Insulation LLC  
One Knauf Drive  
Shelbyville  
IN 46176-1496  
Tel: 800 825 4434  
sds@knaufinsulation.com  
www.knaufinsulation.us

Region: United States, Central & South America's

### **Emergency telephone number**

Emergency telephone: Within United States 24hour: Chemtrec Tel: 800 424 9300

---

## SECTION 2: HAZARDS IDENTIFICATION


### Classification of the substance or mixture

Classification according to the OSHA Hazard Communication Standard (29 CFR 1910.1200):  
The product is not classified.

### Label elements

Contains: None.  
Hazard pictogram: None.  
Signal word: None.  
Hazard statements: None.  
Precautionary statements:  
- Prevention: None.  
- Response: None.  
- Storage: None.  
- Disposal: None.  
Supplemental label information: None.

The following sentences and pictograms are printed on packaging: The mechanical effect of fibers in contact with skin may cause temporary itching.



[www.knaufinsulation.com/comfort-and-handling](http://www.knaufinsulation.com/comfort-and-handling)

### Other hazards

None.

#### Hazard summary

Physical Hazards: None.

Health Hazards: Mechanical irritation of the skin, eyes and upper respiratory system.

Environmental Hazards: None.

Main symptoms: Contact with skin, eyes and upper respiratory system may cause mechanical irritation.  
Biosoluble glass mineral wool is classified as a nuisance dust by OSHA.

Product name:	Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application	Page:	3/12
Revision Date:	2015-06-23	Print date:	2015-10-23
P/N-no.:	KI_DP_112	SDS-ID:	US-EN/1.1

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Substances

<u>%:</u>	<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
93-95	-	Biosoluble glass mineral wool	-	(1), (2), (3)
<1	-	Dedusting Oil	-	(1)
<5	-	Powdered Adhesive	-	(1)
<1	-	Fiber lubricant	-	(1)

Notes:

- (1) Specific chemical identity and/or exact percent concentration is withheld as trade secret.
- (2) Man made vitreous (silicate) fibers with random orientation with alkaline oxide and alkali earth oxide (Na<sub>2</sub>O+K<sub>2</sub>O+CaO+MgO+BaO) content greater than 18% by weight meeting the requirements of Note Q of regulation n° 1272/2008 and therefore not classified carcinogenicity.
- (3) All Knauf Insulation products covered by this SDS are independently certified by EUCEB to be manufactured using biosoluble glass formulations and thus exempt from labeling under NTP or California Prop 65 requirements.

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

#### General Information:

Show this Safety Data Sheet to the medical professional in attendance. If symptoms occur, follow first aid measures as appropriate.

Notes to Physician: None specified.

Inhalation: Remove from exposure. Rinse the throat and clear dust from airways.

Skin contact: If mechanical irritation occurs, remove contaminated clothing and wash skin gently with cold water and soap.

Eye contact: Rinse abundantly with water for at least 15 minutes.

Ingestion: Drink plenty of water if accidentally ingested.

### Most important symptoms and effects, both acute and delayed

Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble glass mineral wool is classified as a nuisance dust by OSHA.

### Indication of any immediate medical attention and special treatment needed

If any adverse reaction or discomfort continues from any of the above exposures, seek professional medical advice.

Product name:	Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application	Page:	4/12
Revision Date:	2015-06-23	Print date:	2015-10-23
P/N-no.:	KI_DP_112	SDS-ID:	US-EN/1.1

---

## **SECTION 5: FIREFIGHTING MEASURES**

### **Extinguishing media**

Water, foam, carbon dioxide (CO<sub>2</sub>), and dry powder.

### **Special hazards arising from the substance or mixture**

Products do not pose a fire hazard in use; however, some packaging materials or facings may be combustible. Products of combustion from product and packaging - carbon dioxide, carbon monoxide and some trace gases such as ammonia, nitrogen oxides and volatile organic substances.

### **Advice for firefighters**

In large fires in poorly ventilated areas involving packaging materials respiratory protection / breathing apparatus may be required.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures**

Personal precautions: Minimize direct contact with skin in order to prevent mechanical itching. In dusty environments, use suitable respiratory protection such as 3M 8210, N95 or equivalent. Use glasses or goggles when working with mineral wool insulation above shoulder height or in dusty environments. Where possible, use natural ventilation during installation in order to minimize dust levels.

After contact with the product, rinse skin in cold water to reduce potential effects of mechanical itching. Dispose of surplus product in accordance with local regulations.

Emergency procedures: Use personal protection recommended in Section 8 of the SDS.

### **Environmental precautions**

Not relevant.

### **Methods and material for containment and cleaning up**

In dusty environments, use vacuum equipment where possible to minimize dust levels.

### **Reference to other sections**

For personal protection, see section 8. For waste disposal, see section 13.

---

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling

Assure proper respiratory protection if dust potential exceeds PEL/TLV.

### Conditions for safe storage, including any incompatibilities

To ensure optimum product performance; when packaging is removed or opened; products should be stored inside or covered to protect them from ingress of rain water or snow. Storage arrangements should ensure stability of stacked products and use on a first in first out basis (FIFO) is recommended.

### Specific end use(s)

Thermal and/or acoustic insulation for use in technical applications, industrial applications and in building construction.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

United States

Occupational exposure limits:

<u>CAS- No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>	<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
-	Glass wool fibers	-	1 fiber/ml	TWA	A3	ACGIH
-	Mineral wool fiber, total particulate	-	5 mg/m3	TWA	-	NIOSH
-	Particulates not otherwise regulated (PNOR), respirable fraction	-	5 mg/m3	TWA	-	OSHA
-	Particulates not otherwise regulated (PNOR), total dust	-	15 mg/m3	TWA	-	OSHA

Notes: (A3) - Fibers longer than 5 µm; diameter less than 3 µm; aspect ratio greater than 5:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.  
- Biosoluble glass mineral wool See section - 3

### Exposure controls

Engineering measures: Maintain sufficient mechanical or natural ventilation to assure fiber concentrations remain below PEL/TLV Use local exhaust if necessary. Power equipment should be equipped with properly designed dust collection devices.

Eye protection: Use glasses or goggles when working with mineral wool insulation above shoulder height or in dusty environments.

Skin protection: Minimize direct contact with skin in order to prevent mechanical itching.

Respiratory equipment: In dusty environments, use suitable respiratory protection.

Hygiene measures: After contact with the product, rinse skin in cold water to reduce potential effects of mechanical itching.

Environmental Exposure Controls: Not relevant.

Product name:	Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application	Page:	6/12
Revision Date:	2015-06-23	Print date:	2015-10-23
P/N-no.:	KI_DP_112	SDS-ID:	US-EN/1.1

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<u>Appearance:</u>	Solid.
<u>Form:</u>	Glass mineral wool fibers in polyethylene bags
<u>Color:</u>	White.
<u>Odor:</u>	Not relevant.
<u>Odor threshold:</u>	Not relevant.
<u>pH:</u>	Not relevant.
<u>Melting point / freezing point:</u>	Not relevant.
<u>Initial boiling point and boiling range:</u>	Not relevant.
<u>Flash point:</u>	Not relevant.
<u>Auto Ignition Temperature (°F)</u>	Not relevant.
<u>Flammability (solid, gas):</u>	Not relevant.
<u>Flammability limit - lower (%):</u>	Not relevant.
<u>Flammability limit - upper (%):</u>	Not relevant.
<u>Vapor pressure:</u>	Not relevant.
<u>Vapor density:</u>	Not relevant.
<u>Evaporation rate:</u>	Not relevant.
<u>Relative density:</u>	Pack density: 161.4 kg/m <sup>3</sup>
<u>Partition coefficient (n-octanol/water):</u>	Not relevant.
<u>Solubility:</u>	Generally chemically inert and insoluble in water.
<u>Decomposition temperature (°F):</u>	Not relevant.
<u>Viscosity:</u>	Not relevant.
—	
<u>Other data:</u>	Devitrification temperature: 1832°F
	Softening temperature: 1112°F
	Nominal diameter of fibers : 2 - 5µm
	Length weight geometric mean diameter less 2 standard errors: < 6 µm
	Orientation of fibers: Random

Product name: Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application  
Revision Date: 2015-06-23  
P/N-no.: KI\_DP\_112

Page: 7/12  
Print date: 2015-10-23  
SDS-ID: US-EN/1.1

---

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity

None.

### Chemical stability

None.

### Possibility of hazardous reactions

None in normal conditions of use.

### Conditions to avoid

None.

### Incompatible materials

Hydrofluoric acid will react with and dissolve glass.

### Hazardous decomposition products

None in normal conditions of use.

---

Product name: Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application Page: 8/12  
Revision Date: 2015-06-23 Print date: 2015-10-23  
P/N-no.: KI\_DP\_112 SDS-ID: US-EN/1.1

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on toxicological effects

Ingestion: Non-hazardous when ingested.  
Inhalation: Mechanical irritation to upper respiratory tract.  
Skin contact: Mechanical irritation to skin.  
Eye contact: Mechanical irritation to eyes.  
Symptoms: Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble glass mineral wool is classified as a nuisance dust by OSHA.

#### Information on toxicological effects:

Acute toxicity: No data were identified for the product as a whole. Data are for constituents:

Product name: Biosoluble glass mineral wool

Result - LD50  
Species - N/A.  
Dose - N/A.  
Exposure - N/A.

Product name: Dedusting Oil

Result - LD50  
Species - N/A.  
Dose - N/A.  
Exposure - N/A.

Product name: Powdered Adhesive

Result - LD50  
Species - N/A.  
Dose - N/A.  
Exposure - N/A.

Product name: Fiber lubricant

Result - LD50  
Species - N/A.  
Dose - N/A.  
Exposure - N/A.

Serious eye damage/irritation: May cause mechanical irritation to eyes.  
Skin Corrosion/Irritation: May cause mechanical irritation to skin.  
Respiratory or skin sensitization: No data were identified for this product or its constituents.  
Germ cell mutagenicity: No data were identified for this product or its constituents.

Carcinogenicity: Results from a biopersistence test by intratracheal instillation has shown that fibers in this product longer than 20 µm have a weighted half-life less than 40 days, thus this product is not classified as a carcinogen. None of the components of this product are listed as a carcinogen by OSHA, IARC or NTP.

Reproductive Toxicity: No data were identified for this product or its constituents.  
Developmental Effects: No data were identified for this product or its constituents.  
STOT - Single exposure: No data were identified for this product or its constituents.  
STOT - Repeated exposure: No data were identified for this product or its constituents.  
Aspiration hazard: Not relevant.



Product name:	Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application	Page:	9/12
Revision Date:	2015-06-23	Print date:	2015-10-23
P/N-no.:	KI_DP_112	SDS-ID:	US-EN/1.1

---

## SECTION 12: ECOLOGICAL INFORMATION

### **Toxicity**

**Ecotoxicity:** This product is not ecotoxic to air, water or soil, by composition.

### **Persistence and degradability**

Inert inorganic product - <7% Organic Content.

### **Bioaccumulative potential**

Will not bio-accumulate.

### **Mobility in soil**

Not considered mobile. Less than 1% leachable organic carbon if landfilled.

### **Results of PBT and vPvB assessment**

Not relevant.

### **Other adverse effects**

None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### **Waste treatment methods**

**Waste from residues:** Dispose of in accordance with all applicable regulations.

**Contaminated packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**Disposal methods:** This product is not regulated under RCRA Hazardous Waste Regulations. May be disposed in landfill. If unsure, contact the local office of the USEPA, your local public health department or the local landfill regulators.

---

Product name: Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application  
Revision Date: 2015-06-23  
P/N-no.: KI\_DP\_112

Page: 10/12  
Print date: 2015-10-23  
SDS-ID: US-EN/1.1

---

## SECTION 14: TRANSPORT INFORMATION

### UN number

Not regulated.

### UN proper shipping name

Not regulated.

### Transport hazard class(es)

Not regulated.

### Packing group

Not regulated.

### Environmental hazards

Not regulated.

### Special precautions for user

Not regulated.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not regulated.

---

Product name:	Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application	Page:	11/12
Revision Date:	2015-06-23	Print date:	2015-10-23
P/N-no.:	KI_DP_112	SDS-ID:	US-EN/1.1

---

## **SECTION 15: REGULATORY INFORMATION**

### **Safety, health and environmental regulations/legislation specific for the substance or mixture**

OSHA Status: This product is regulated as a nuisance dust under OSHA criteria. Classified as not hazardous.

TSCA listed: All components of this product are listed or exempt from listing on the TSCA inventory.

CERCLA Reportable Quantity: Not regulated.

SARA Title III:

Section 302 Extremely Hazardous: Not regulated.

Section 311/312 Hazard Categories: Not regulated.

Section 313 Toxic Chemicals: Not listed.

California Safe Drinking Water and Toxic Enforcement Act (Prop. 65): This product is exempt from labeling requirements under this Act.

In accordance with industry practice, Knauf Insulation has decided to continue to provide its customers with the appropriate information for the purpose of assuring safe handling and use of mineral wool throughout the product life.

—

---

Product name:	Glass Blowing Mineral Wool Insulation with Adhesive for Spray Application	Page:	12/12
Revision Date:	2015-06-23	Print date:	2015-10-23
P/N-no.:	KI_DP_112	SDS-ID:	US-EN/1.1

---

## SECTION 16: OTHER INFORMATION

Label in accordance with OSHA HCS (2012): The product is not classified.

Abbreviations and acronyms used in the safety data sheet:

CAS: Chemical Abstract Service  
CFR: Code of Federal Regulations  
EUCEB: European Certification Board for Mineral Wool Products  
IARC: International Agency for Research on Cancer  
NTP: National Toxicology Program  
OSHA: Occupational Safety and Health Administration (United States)  
PEL: Permissible Exposure Limit  
PBT: Persistent, Bioaccumulative and Toxic  
SARA: Superfund Amendments and Reauthorization Act  
SDS: Safety Data Sheet  
STEL: Short Term Exposure Limit  
TLV: Threshold Limit Value  
TSCA: Toxic Substances Control Act  
USEPA: United States Environmental Protection Agency

All products manufactured by Knauf Insulation are made of non-classified fibers and are certified by EUCEB.

Products meeting EUCEB certification requirements can be recognised by the EUCEB logo printed on the packaging.

Further information can be obtained from:

[www.euceb.org](http://www.euceb.org)  
[www.knaufinsulation.com](http://www.knaufinsulation.com)



Additional information:

Change to Sections: 8, 11  
New document format - Date: 2015-10-23  
Date of previous revisions: 2015-06-22

Moreover, in 2001, the IARC, reclassified glass mineral wool fibers from Group 2B (possibly carcinogenic) to «not classifiable as to their carcinogenicity to humans (Group 3)». (See Monograph Vol 81, <http://monographs.iarc.fr/>).

---

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

---