



INSULATION CERTIFICATE



COVERAGE INFORMATION

R-Value*	Bags Per 1000 Ft ²	Maximum Coverage	Minimum Density	Installed Thickness
To obtain an insulation resistance (R) of:	No. of bags per 1,000 ft ² shall not be less than:	Contents of bag shall not cover more than: (ft ²)	Weight per square foot shall not be less than: (lbs/ft ²)	Installed insulation shall not be less than: (in)
R-60	45	22	1.336 lbs.	19.50
R-49	37	27	1.094 lbs.	16.00
R-44	33	30	0.998 lbs.	14.25
R-38	28	35	0.849 lbs.	12.25
R-30	23	44	0.683 lbs.	9.75
R-22	16	61	0.489 lbs.	7.00
R-21	15	67	0.448 lbs.	6.75
R-19	14	71	0.425 lbs.	6.25
R-13	10	101	0.297 lbs.	4.25
R-11	9	117	0.255 lbs.	3.50

*R means resistance to heat flow. The higher the R-value, the greater the insulation power. Ask your seller for the fact sheet on R-values. Nominal bag weight 30 lbs. For pneumatic application only. Thermal resistance values are determined in accordance with ASTM C 518. This product meets or exceeds the requirements of ASTM C 1014 and ASTM C 764 Type 1.

Builder's and Applicator's Certification Signature

This is to certify the insulation as installed conforms to the requirements indicated on this card to provide thermal resistance value of R _____ using _____ bags of insulation to cover _____ square feet area.

Depth of previous insulation _____ Inches, R _____ R-value. Type of insulation: _____ Upgrade New Construction
Mineral Wool, Fiberglass, etc.

 Date Company Name (Builder) Address Phone Builder's Signature

 Date Company Name (Applicator) Address Phone Builder's Signature